



TANDBERG Telepresence T1

The instant telepresence experience designed for the executive office or high-end collaboration room — available anytime you need it. With optimal camera height, an enormous LCD screen and crystal-clear video, the TANDBERG T1 delivers an unparalleled user experience and enables executives to truly see eye-to-eye.



Powered by the ultimate telepresence engine, the TANDBERG Codec C90

ULTIMATE DESIGN FOR INSTANT TELEPRESENCE

- Exclusive Scandinavian design
- Ultimate quality in video and audio — high definition up to 1080p with large 65" custom LCD screen
- Revolutionary user experience
- Excellent eye contact and ideal screen height
- Appealing, natural user interface
- UX GA high-definition presentation capabilities
- 720p30 HD Individual Transcoding embedded Multisite
- H.323/SIP up to 6 Mbps point-to-point; up to 10 Mbps total MultiSite bandwidth
- Full duplex audio with high-quality stereo sound
- Ideal for smaller telepresence studios, executive offices, high-end conference rooms and the showroom floor
- Unmatched room and network flexibility — use it where you need it

CONNECT TO ANYONE...AT ANYTIME...ANY WAY

With the TANDBERG Telepresence T1, telepresence no longer limits who you can talk to and how. The boundaries of dissimilar networks, multi-vendor systems, inconsistent quality and functional complexity are eliminated so that colleagues, customers and partners can communicate with total ease. Standards-compliant technology makes it all happen.

GET THE MOST FROM YOUR INVESTMENT. WITH **PROFESSIONAL SERVICES**, TANDBERG EXPERTS SUPPORT TANDBERG TELEPRESENCE DEPLOYMENT AND TRAINING. VISIT WWW.TANDBERG.COM

UNIT DELIVERED COMPLETE WITH:

65" custom LCD screen, wireless remote control, TANDBERG PrecisionHD 1080p camera, microphone, integrated speakers, integrated cabling

BANDWIDTH

H.323/SIP up to 6 Mbps point-to-point
Up to 10 Mbps total MultiSite bandwidth

FIREWALL TRAVERSAL

TANDBERG Expressway™ Technology
H.460.18, H.460.19 Firewall Traversal

VIDEO STANDARDS

H.263, H.263+, H.264

VIDEO FEATURES

Native 16:9 Widescreen
Advanced Screen Layouts
Intelligent Video Management
Local Auto Layout

VIDEO INPUTS (13 INPUTS)

4 X HDMI INPUTS SUPPORTING RESOLUTIONS:

1920 x 1080@30fps (HD1080p30)
1920 x 1080@60fps (HD1080p60)
1920 x 1080@50fps (HD1080p50)
1280 x 720@60fps (HD720p60)
1920 x 1080@25fps (HD1080p25)
1920 x 1080@24fps (HD1080p24)
1280 x 720@50fps (HD720p50)

4 X HD-SDI INPUTS SUPPORTING RESOLUTIONS:

1920 x 1080@30fps (HD1080p30)
1280 x 720@60fps (HD720p60)
1920 x 1080@25fps (HD1080p25)
1280 x 720@50fps (HD720p50)

2 X DVI-I INPUTS, SUPPORTING RESOLUTIONS:

640 x 480@60fps (VGA)
800 x 600@60fps (SVGA)
1024 x 768@60fps (XGA)
1280 x 768@60fps (WXGA)
1280 x 1024@60fps (SXGA)
1440 x 900@60fps (WSXGA)
1400 x 1050@60fps (SXGA+)
UXGA*

2 X YPbPr INPUTS, SUPPORTING RESOLUTIONS:

1920 x 1080@30fps (HD1080p30)
1280 x 720@60fps (HD720p60)
1920 x 1080@25fps (HD1080p25)
1280 x 720@50fps (HD720p50)

1 x S-Video/Composite input (BNC connectors)

PAL/NTSC

Extended Display Identification Data (EDID)

VIDEO OUTPUTS (5 OUTPUTS)

2 X HDMI OUTPUTS, 2 X DVI-I OUTPUTS, 1 X COMPOSITE OUTPUT
(BNC CONNECTOR) PAL/NTSC SUPPORTING RESOLUTIONS:

1920 x 1080@60fps (HD1080p60)
1280 x 720@60fps (HD720p60)
1366 x 768@60fps (WXGA)
1280 x 768@60fps (WXGA)
1440 x 900@60fps (WSXGA)
1280 x 1024@60fps (SXGA)
1024 x 768@60fps (XGA)

VESA Monitor Power Management

LIVE VIDEO RESOLUTIONS (ENCODE/DECODE)

176 x 144@30fps (QCIF)
352 x 288@30fps (CIF)
576 x 448@30fps (448p)
768 x 448@30fps (w448p)
512 x 288@30fps (w288p)
704 x 576@30fps (4CIF)
1024 x 576@30fps (w576p)
640 x 480@30fps (VGA)
800 x 600@30fps (SVGA)
1024 x 768@30fps (XGA)
1280 x 1024@30fps (SXGA)
1280 x 768@30fps (WXGA)
1440 x 900@30fps (WSXGA)
1280 x 720@30fps (HD720p30)
1920 x 1080@30fps (HD1080p30)**

AUDIO STANDARDS

G.711, G.722, G.722.1, 64 bit & 128 bit MPEG4 AAC-LD,
AAC-LD Stereo

AUDIO FEATURES

CD-Quality 20KHz Mono and Stereo
Eight separate acoustic echo cancellers
8-port Audio mixer
Automatic Gain Control (AGC)
Automatic Noise Reduction
Active lip synchronization
GSM/Blackberry interference audio feature

AUDIO INPUTS (16 INPUTS)

8 x microphone, 24V phantom powered, XLR connector
each with separate echo cancellers and noise reduction,
all microphones can be set for balanced line level
2 x RCA/Phono, Line Level: Stereo PC input
2 x RCA/Phono, Line Level: Stereo auxiliary/DVD input
4 x HDMI, digital: Stereo PC/DVD inputs

AUDIO OUTPUTS (8 OUTPUTS)

2 x XLR, balanced line level, stereo main audio
2 x RCA/Phono, line level, stereo main audio, configurable
to S/PDIF
2 x RCA/Phono, line level, stereo to recording device
1 x HDMI, digital, stereo main audio
1 x HDMI, digital, stereo to recording device

DUAL STREAM

H.239 (H.323) dual stream
BFCP (SIP) dual stream
Available in MultiSite from any site

MULTISITE FEATURES

4-way High Definition SIP/H.323 MultiSite
Full individual audio and video transcoding
H.323/SIP/VoIP in the same conference
Best Impression (Automatic CP Layouts)
H.264, Encryption, Dual Stream from any site
IP Downspeeding
Dial in/Dial out
Conference rates up to 10 Mbps

PROTOCOLS

H.323
SIP

EMBEDDED ENCRYPTION

H.323/SIP point-to-point and multipoint calls
Standards-based: H.235 v2 & v3 and AES
Automatic key generation and exchange
Supported in Dual Stream & MultiSite

IP NETWORK FEATURES

DNS lookup for service configuration
Differentiated Services (QoS)
IP adaptive bandwidth management (including flow control)
Auto gatekeeper discovery
Dynamic play-out and lip-sync buffering
H.245 DTMF tones in H.323
Date and Time support via NTP
Packet Loss based Downspeeding
URI Dialing

SECURITY FEATURES

Management via HTTPS and SSH
IP Administration Password
Menu Administration Password
Disable IP services
Network Settings protection

NETWORK INTERFACES

2*** x separate LAN/Ethernet (RJ-45) 100/1000 Mbit
USB host for future usage
USB device for future usage

ETHERNET/INTERNET/INTRANET CONNECTIVITY

TCP/IP, DHCP, Telnet, HTTP, HTTPS, SOAP and XML

PRECISION HD 1080P CAMERA

1/3" CMOS
12 x zoom
+15°/-25° tilt, +/- 90° pan
43.5° vertical field of view
72° horizontal field of view
Focus distance 0.3m-infinity
1920 x 1080 pixels progressive @ 60fps
Automatic or manual focus/brightness/whitebalance
Far-end camera control
15 near and far-end camera presets
Daisy-chain support (Visca protocol camera)
Dual HDMI and HD-SDI output
Upside-down mounting with automatic flipping of picture

SYSTEM MANAGEMENT

Support for the TANDBERG Management Suite
Total management via embedded SNMP, Telnet, SSH, XML, SOAP
Remote software upload: via web server, SCP, HTTP, HTTPS
1 x RS-232 local control and diagnostics
Remote control and on-screen menu system

DIRECTORY SERVICES

Support for Local directories (My Contacts)
Corporate Directory
Unlimited entries using Server directory supporting
LDAP and H.350
Unlimited number for Corporate directory (through TMS)
200 number local directory
Received Calls
Placed Calls
Missed Calls with Date and Time

POWER

Auto-sensing power supply
100-240 VAC, 50/60 Hz
175 watts max. for codec and main camera

OPERATING TEMPERATURE AND HUMIDITY

0° C to 35° C (32° F to 95° F) ambient temperature
10% to 90% Relative Humidity (RH)

STORAGE AND TRANSPORT TEMPERATURE

-20° C to 60° C (-4° F to 140° F) at RH 10-90% (non-condensing)

DIRECTORY SERVICES

Directive 73/23/EEC (Low Voltage Directive)
— Standard EN 60950
Directive 89/336/EEC (EMC Directive)
— Standard EN 55022, Class B
— Standard EN 55024
— Standard EN 61000-3-2/-3-3
Approved according to UL 60950 and CAN/CSA C22.2 No.60950
Complies with FCC15B Class B

UNIT DIMENSIONS

Height: 165 cm (65 inches)
Width: 150 cm (59.1 inches)
Depth: 15 cm (5.9 inches)
Weight: 150 kg (330 lbs)

* requires option

** requires option

*** only one LAN/Ethernet interface supported in version 1

All specifications subject to change without notice, system specifics may vary.

All images in these materials are for representational purposes only, actual products may differ.

TANDBERG and Expressway are registered trademarks or trademarks of TANDBERG in the U.S. and other countries.

All other trademarks are property of their respective owners.


MTBF PRODUCT RELIABILITY/MTBF

The predicted reliability is expressed in the expected random Mean Time Between Failures (MTBF) for the electronic components based on the Power On Hours:

Power On Hours (POH) > 69 000 hours

Useful Life Cycle > 6 years

ISO 9001 certificate is available upon request



TANDBERG

Telepresence T1

TANDBERG WORLD HEADQUARTERS

Philip Pedersens vei 20
1366 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 126 126
tandberg@tandberg.com

1212 Avenue of the Americas,
24th Floor
New York, NY USA 10036
Tel: +1 212 692 6500
Fax: +1 212 692 6501
Video: +1 212 692 6535
tandberg@tandberg.com

September 2008